

Product: Style AG216 Acrylic Transfer Tape

AG216 is a 5 mil high tack acrylic transfer adhesive that adheres well to many plastic, rubber, and foam substrates. AG216 is supplied on a 80# Kraft liner.

Specifications:

Color	Transparent
Total Thickness	.0095" (+/- 10%)
Liner Thickness	.0045" (80#)
Adhesion to Steel (PSTC 3) Modified	100 oz/in width
Operating Temperature	-30° F to +225° Fahrenheit
Shelf Life	1 Year @ 50% humidity and 72° Fahrenheit

Adhesion to Closed Cell Sponge Rubber - Good

Adhesion to Open Cell Sponge Rubber – Fair / Good

Adhesion to Open Cell Urethane Foam – Good

Adhesion to Polar Material – Good

Adhesion to Low Surface Energy Material – Fair / Good

Modification PSTC 3:

30 minute dwell

2.5 mil non-coated densified Kraft paper for a support backing.

Product Testing:

The performance data represented are based on reliable laboratory tests. Test conditions cannot always duplicate actual field installations or end uses. Atlantic Gasket makes no warranties with respect to test data, and assumes no responsibility for performance characteristics resulting from conditions, which differ from those, used in laboratory tests. Each user should make independent tests to determine the suitability of this product for the intended use.