

**Product: Style AG2318 Rubber Based Double Coated Polyester**

AG2318 is a polyester film coated on two sides with an aggressive permanent pressure sensitive rubber based adhesive protected by a two-side release treated liner.

**Application:** This product is designed for bonding to urethane foam, closed cell sponge rubber, polyethylene foam, cork, felt, and a wide range of bonding applications. This product also meets the requirements of FDA 21 CFR 175.105.

**Typical test data:**

Thickness	Exposed side: 1.6 mils Carrier: 0.5 mils Liner side: 1.4 mils
Peel Adhesion	Exposed side: 104 oz. Liner side: 120 oz.
Probe tack	Exposed side: 1700 grams Liner side: 2100 grams
SAFT	Exposed side: 170 °F Liner side: 170 °F
Liner	80# Kraft
Shelf Life	<p>Although a specific shelf life limitation has not been established, the following guidelines are offered for consideration in extending the useful storage of supplied product up to one year.</p> <ol style="list-style-type: none"> <li>1. Material should be kept relatively clean, and free from mechanical damage.</li> <li>2. For maximum protection and extended storage material should be kept in storage not affected by weather conditions, with a temperature no greater then 72 °F. and a maximum relative humidity of 50%.</li> </ol>

**Product Testing:**

The performance data represented are based on reliable laboratory tests. Test conditions cannot always duplicate actual field installations or end uses. Atlantic Gasket makes no warranties with respect to test data, and assumes no responsibility for performance characteristics resulting from conditions, which differ from those, used in laboratory tests. Each user should make independent tests to determine the suitability of this product for the intended use.