

## Product: Style AG315 Double Coated Non Woven Tape

AG315 is a double coated non woven tape. Coated with a permanent high tack acrylic adhesive on both sides, it laminates well to many rubber, foam and plastic substrates. AG315 is specifically designed for applications where an excellent balance of high peel and shear is necessary.

### Specifications:

Color	Transparent
Total Thickness	.0105" (+/- 10%)
Liner Thickness	.0045" (80#)
Carrier Thickness	.003"
Adhesion to Steel	Liner Side                      80oz/in width
(PSTC 3) Modified	Exposed Side                      80oz/in width
Operating Temperature	-34° F to +225° Fahrenheit
Shelf Life	1 Year @ 50% humidity and 72° Fahrenheit

**Adhesion to Closed Cell Sponge Rubber - Good**  
**Adhesion to Open Cell Sponge Rubber – Good**  
**Adhesion to Open Cell Urethane Foam – Good**  
**Adhesion to Polar Material – Good**  
**Adhesion to Low Surface Energy Material – Fair / Good**

**Modification PSTC 3:**  
**30 minute dwell**  
**2.5 mil non-coated densified Kraft paper for a support backing.**

### Product Testing:

The performance data represented are based on reliable laboratory tests. Test conditions cannot always duplicate actual field installations or end uses. Atlantic Gasket makes no warranties with respect to test data, and assumes no responsibility for performance characteristics resulting from conditions, which differ from those, used in laboratory tests. Each user should make independent tests to determine the suitability of this product for the intended use.